



Parquet Prime



Parquet Prime is a one component acrylic primer for use on wooden floors prior to application of Parquet One, Parquet Pro and Parquet Performance.

- Gives good build, enhances the overall appearance
- Reduces risk of sidebonding
- Fast drying

Enhancing the appearance of your floor

A fast drying primer giving excellent build

Uses

A waterborne one pack acrylic primer, formulated to prime wooden floors, prior to coating with Parquet One, Parquet Pro or Parquet Performance. It enhances the colour of the timber, improves the overall build of the finish and reduces the risk of sidebonding.

Always stir well before use.

Preparation

New Floors:

The surface to be finished must be clean, dry and free from contamination.

Pre-sand using 100 or 120 grit paper and remove sanding dust prior to application.

Previously Finished Floors:

Sand the floor back to bare timber, removing all the old coating, then treat as a new floor.

Application

Apply by brush or lambs wool mop applicator.

Ensure an even application of the primer, avoiding leaving thick areas of sealer.

Do not use in areas of high humidity or condensation.

If needed, a light sanding may be carried out before applying further coats.

Drying

Recoat after 1 to 2 hours under normal drying conditions (20°C and 60% RH).

Drying times will be extended under conditions of low temperature or high humidity.

A minimum temperature of 15°C is needed during application and drying.

Other

Coverage

8 – 12 sq. metres per litre depending upon the surface and application.

Cleaning Equipment

Tools, brushes etc. may be cleaned using water containing a small amount of detergent.

Storage

Store away from frost and direct sunlight.

Health & Safety

Refer to separate health and safety data sheets. For professional use only.

